



product code: B2B-BAZA23-SPP155F-X

## POLISH PRODUCT

SPARTUS® ProFLEX handles are produced in Poland.

### Product variants

Index	Price
ProTIG 155F configurator B2B-BAZA23-SPP155F-X	€205.65 / pc Net price

### Product description

## SPARTUS® PROFLEX TIG 155F HAND TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

## CABLES



In the production of **SPARTUS® ProFLEX** handles, a professional

cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.



## CABLE PACKAGES

In **SPARTUS® ProFLEX** holders, 3 types of cable covers can be used. The "T" and "U" packages are manufactured in a textile-polyester cover, while the "X" package is made in a textile-rubber cover. The "U" and "X" packages also have a one-meter section of leather behind the handle.



textile-polyester cover



textile-rubber cover

## REPLACEABLE TORCH HEADS

Replaceable **SPARTUS®** torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs - size of the head, angle of inclination. In the SP155F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

## LONG NECK TIG

Long Neck TIG is a specially designed torch extension system. Increasing the range and flexibility of extensions allows for efficient welding of places where classic solutions fail.



## PARTS SET

All **SPARTUS® ProFLEX** holders are supplied with consumables in a handy box.

*The presented handle image in the article is for illustrative purposes and depends on the options selected in the configurator and related products.*

## Technical details

<b>Duty cycle</b>	<b>80%</b>
<b>Rating</b>	<b>125A DC 100A AC</b>
<b>Electrode diameter</b>	<b>0.5, 1.0, 1.6, 2.0, 2.4mm</b>
<b>Gas flow rate</b>	<b>7 - 15 l/min</b>
<b>Cooling type</b>	<b>gas</b>
<b>Standard</b>	<b>9 [small consumables], replaceable torch heads</b>