

Product details: TIG 9V torch, 4m, Easy series, control in the handle, package X, SPARTUS® connection

product code: **SPE9V-4-mSRE1B-X-8SPA**



Product variants

| Index | Price |
|--|---------------------------------|
| TIG 9V torch, 4m, Easy series, control in the handle, package X, SPARTUS® connection SPE9V-4-mSRE1B-X-8SPA | €62.79 / pc Net price |
| TIG 9V torch, 4m, Easy series, control in the handle, package D, SK35, 30cm hose, Rec6 SPE9V-4-mSRE1B-D-1BEZ | €47.00 / pc Net price |
| TIG 9V torch, 4m, Easy series, control in the handle, package D, SPARTUS® connection SPE9V-4-mSRE1B-D-8SPA | €52.28 / pc Net price |
| TIG 9V torch, 4m, Easy series, control in the handle, package X, SK35, 30cm hose, Rec6 SPE9V-4-mSRE1B-X-1BEZ | €57.50 / pc Net price |

Product description

SPARTUS® EASYTIG TORCH 9V with valve and controls in the handle

The **SPARTUS® EasyTIG** series is a classic solution of welding torches designed with simplicity and ergonomics in mind.

TORCH BODIES

The torch body equipped with a valve allows for smooth regulation of the gas stream depending on the specific requirements of the welder.

HANDLES

Handle with a single microswitch, dedicated to work with machines equipped with a control connector for contactless ignition.

WIRE PACKAGE

For solutions with control in the handle, a cable package is available, marked with the X symbol, which is in a textile and rubber cover with a piece of leather behind the handle. Package comes with a basic set of consumables.



CONNECTIONS

A wide range of connections enables the use of **SPARTUS® EasyTIG** torches with a valve and control in the handle with the most popular welding devices available on the European market.

The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

| | |
|---------------------------|------------------------------|
| Rating | 125A DC 100A AC |
| Electrode diameter | 0.5 - 2.4mm |
| Gas flow rate | 7 - 15 l/min |
| Duty cycle | 35% |
| Cooling type | gas |
| Standard | 9 [small consumables] |
| Length | 4m |
| Control plug | 8SPA - SPARTUS® |