

SP17 EASY

product code: SPE17-4-mSRE1B-X-1FRO



Product variants

Index

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to FRONIUS®

SPE17-4-mSRE1B-X-1FRO

TIG torch 17, 4m, Easy series, mini 1B, package X, SK35, 30cm hose, Rec6

SPE17-4-MSRE1B-X-1BEZ

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to ESAB®

SPE17-4-mSRE1B-X-1ESB

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to EWM®

SPE17-4-mSRE1B-X-1EWM

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to FALTIG®

SPE17-4-mSRE1B-X-1FAL

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to KEMPPi®

SPE17-4-mSRE1B-X-1KMP

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to LINCOLN®

SPE17-4-mSRE1B-X-1LIN

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to MAGNUM®

SPE17-4-mSRE1B-X-1MAG

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to ESAB®

SPE17-4-mSRE1B-X-2ESB

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to FRONIUS®

SPE17-4-mSRE1B-X-2FRO

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to KEMPPi®

SPE17-4-mSRE1B-X-2KMP

TIG torch 17, 4m, Easy series, mini 1B, package X, control plug fit to MAGNUM®

SPE17-4-MSRE1B-X-2MAG

TIG torch 17, 4m, Easy series, mini 1B, package X, SPARTUS® control plug

SPE17-4-MSRE1B-X-8SPA

TIG torch 9, 4m, Easy series, mini 1B, package X, SPARTUS® control plug

SPE17-4-mSRE1B-X-9SPA

Product description

SPARTUS® EASYTIG 17 TORCH

The **SPARTUS® EasyTIG** series is a classic solution of welding torches designed with simplicity and ergonomics in mind.

TORCH BODIES

Easy series torches are offered with a standard torch body (or a flexible version available in the configurator).

HANDLES

The handle used in the **SPARTUS® Easy** holder, thanks to its ergonomic design and non-slip lining, provides comfort and a high level of control, necessary for precise guidance of the torch.

WIRE PACKAGE

In **EasyTIG** torches, the set of cables, marked with the X symbol, is in a textile-rubber sheath with a section of leather behind the handle and a basic set of consumables.

CONNECTIONS

A wide range of connections enables the use of SPARTUS® torches with the most popular welding devices available on the European market.



The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	150A DC 115A AC
Electrode diameter	0.5 - 3.2mm
Gas flow rate	7 - 15l/min
Duty cycle	35%
Cooling type	gas
Standard	17 [large consumables]
Length	4m
Control plug	1FRO - fit FRONIUS®