

Product details: TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to MAGNUM®

SP20 EASY

product code: SPE20-4-mSRE1B-X-2MAG



Product variants

Index

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to MAGNUM®
SPE20-4-mSRE1B-X-2MAG

TIG 20 torch, 4m, Easy series, mini 1B, X package, SK35, 30cm hose, Rec6
SPE20-4-mSRE1B-X-1BEZ

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to ESAB®
SPE20-4-mSRE1B-X-1ESB

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to EWM®
SPE20-4-mSRE1B-X-1EWM

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to FRONIUS®
SPE20-4-mSRE1B-X-1FRO

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to KEMPPI®
SPE20-4-mSRE1B-X-1KMP

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to LINCOLN®
SPE20-4-mSRE1B-X-1LIN

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to MAGNUM®
SPE20-4-mSRE1B-X-1MAG

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to ESAB®
SPE20-4-mSRE1B-X-2ESB

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to FRONIUS®
SPE20-4-mSRE1B-X-2FRO

TIG 20 torch, 4m, Easy series, mini 1B, X package, control plug fit to KEMPPI®
SPE20-4-mSRE1B-X-2KMP

TIG 20 torch, 4m, Easy series, mini 1B, X package, SPARTUS® control plug
SPE20-4-mSRE1B-X-8SPA

TIG 20 torch, 4m, Easy series, mini 1B, X package, SPARTUS® control plug
SPE20-4-mSRE1B-X-9SPA

Product description

SPARTUS® EASYTIG 20 TORCH

The **SPARTUS® EasyTIG** series is a classic solution of welding torches designed with simplicity and ergonomics in mind.

TORCH BODIES

Easy series torches are offered with a standard torch body (or a flexible version available in the configurator).

HANDLES

The handle used in the **SPARTUS® Easy** holder, thanks to its ergonomic design and non-slip lining, provides comfort and a high level of control, necessary for precise guidance of the torch.

WIRE PACKAGE

In **EasyTIG** torches, the set of cables, marked with the X symbol, is in a textile-rubber sheath with a section of leather behind the handle and a basic set of consumables.

CONNECTIONS

A wide range of connections enables the use of SPARTUS® torches with the most popular welding devices available on the European market.



The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	250A DC 200A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4, 3.2mm
Gas flow rate	7 - 20 l/min
Liquid cooling flow	1.0 - 1.5 l/min
Duty cycle	80%
Cooling type	liquid
Standard	20/25 [small consumables]
Length	4m
Control plug	2MAG - fit MAGNUM®