

Product details: TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6



product code: SPP225FA-4-mSRP1B-U-1BEZ

## POLISH PRODUCT

Torches **SPARTUS®** **ProFLEX** brand are made in Poland

## Product variants

### Index

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6**  
**SPP225FA-4-mSRP1B-U-1BEZ**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB®**  
**SPP225FA-4-mSRP1B-U-1ESB**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit EWM®**  
**SPP225FA-4-mSRP1B-U-1EWM**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS®**  
**SPP225FA-4-mSRP1B-U-1FRO**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI®**  
**SPP225FA-4-mSRP1B-U-1KMP**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit LINCOLN®**  
**SPP225FA-4-mSRP1B-U-1LIN**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM®**  
**SPP225FA-4-mSRP1B-U-1MAG**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB®**  
**SPP225FA-4-mSRP1B-U-2ESB**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS®**  
**SPP225FA-4-mSRP1B-U-2FRO**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI®**  
**SPP225FA-4-mSRP1B-U-2KMP**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM®**  
**SPP225FA-4-mSRP1B-U-2MAG**

---

**TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug**  
**SPP225FA-4-mSRP1B-U-8SPA**

---

<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug</b> <b>SPP225FA-4-mSRP1B-U-9SPA</b>
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS®</b> <b>SPP225FA-4-mSRP4B-X-9SPA</b>
<b>TIG 225F torch with SP9-70 head, 8m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS®</b> <b>SPP225FA-8-mSRP4B-X-9SPA</b>

Product description

SPARTUS® PROFLEX TIG 255F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES



In  
the

production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

REPLACEABLE TORCH HEADS

Replaceable SPARTUS® torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs - size of the head, angle of inclination. In the SP255F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

*The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.*

Technical details

Rating	125A DC 100A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4mm
Gas flow rate	7 - 20L/min
Liquid cooling floww	1.0 - 1.5L/min
Duty cycle	100%
Cooling type	liquid
Standard	225F [small consumables]
Length	4m
Control plug	SK35, 2m hose, 1/4 nut