

Product details: TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS®



product code: SPP225FA-4-mSRP1B-U-1FRO

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

Product variants

Index	Price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS® SPP225FA-4-mSRP1B-U-1FRO	€272.18 / pc VAT 23% €334.78 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6 SPP225FA-4-mSRP1B-U-1BEZ	€260.94 / pc VAT 23% €320.96 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP225FA-4-mSRP1B-U-1ESB	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit EWM® SPP225FA-4-mSRP1B-U-1EWM	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI® SPP225FA-4-mSRP1B-U-1KMP	€272.18 / pc VAT 23% €334.78 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit LINCOLN® SPP225FA-4-mSRP1B-U-1LIN	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP225FA-4-mSRP1B-U-1MAG	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP225FA-4-mSRP1B-U-2ESB	€322.75 / pc VAT 23% €396.98 / pc

Index	Price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS® SPP225FA-4-mSRP1B-U-2FRO	€322.75 / pc VAT 23% €396.98 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI® SPP225FA-4-mSRP1B-U-2KMP	€322.75 / pc VAT 23% €396.98 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP225FA-4-mSRP1B-U-2MAG	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug SPP225FA-4-mSRP1B-U-8SPA	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug SPP225FA-4-mSRP1B-U-9SPA	€267.96 / pc VAT 23% €329.59 / pc
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS® SPP225FA-4-mSRP4B-X-9SPA	€282.61 / pc VAT 23% €347.61 / pc
TIG 225F torch with SP9-70 head, 8m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS® SPP225FA-8-mSRP4B-X-9SPA	€325.76 / pc VAT 23% €400.68 / pc

Product description

SPARTUS® PROFLEX TIG 255F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES



production of **SPARTUS® ProFLEX** torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

REPLACEABLE TORCH HEADS

Replaceable SPARTUS® torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs - size of the head, angle of inclination. In the SP255F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	125A DC 100A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4mm
Gas flow rate	7 - 20L/min

Liquid cooling floow	1.0 - 1.5L/min
Duty cycle	100%
Cooling type	liquid
Standard	225F [small consumables]
Length	4m
Control plug	1FRO - fit FRONIUS®