

Product details: TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM®



product code: SPP225FA-4-mSRP1B-U-2MAG

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

Product variants

Index	Price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP225FA-4-mSRP1B-U-2MAG	€267.96 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6 SPP225FA-4-mSRP1B-U-1BEZ	€260.94 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP225FA-4-mSRP1B-U-1ESB	€267.96 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit EWM® SPP225FA-4-mSRP1B-U-1EWM	€267.96 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS® SPP225FA-4-mSRP1B-U-1FRO	€272.18 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI® SPP225FA-4-mSRP1B-U-1KMP	€272.18 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit LINCOLN® SPP225FA-4-mSRP1B-U-1LIN	€267.96 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP225FA-4-mSRP1B-U-1MAG	€267.96 / pc Net price
TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP225FA-4-mSRP1B-U-2ESB	€322.75 / pc Net price

Index	Price
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS®</b> SPP225FA-4-mSRP1B-U-2FRO	<b>€322.75</b> / pc Net price
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI®</b> SPP225FA-4-mSRP1B-U-2KMP	<b>€322.75</b> / pc Net price
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug</b> SPP225FA-4-mSRP1B-U-8SPA	<b>€267.96</b> / pc Net price
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug</b> SPP225FA-4-mSRP1B-U-9SPA	<b>€267.96</b> / pc Net price
<b>TIG 225F torch with SP9-70 head, 4m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS®</b> SPP225FA-4-mSRP4B-X-9SPA	<b>€282.61</b> / pc Net price
<b>TIG 225F torch with SP9-70 head, 8m, ProFLEX series, mini 4B, X package, control plug fit to SPARTUS®</b> SPP225FA-8-mSRP4B-X-9SPA	<b>€325.76</b> / pc Net price

Product description

SPARTUS® PROFLEX TIG 255F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES



production of **SPARTUS® ProFLEX** torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In **SPARTUS® ProFLEX** holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

TOOLBOX

**SPARTUS® ProFLEX** torches are equipped with a handy box containing consumables (toolbox).

REPLACEABLE TORCH HEADS

Replaceable **SPARTUS®** torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs - size of the head, angle of inclination. In the SP255F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, **SPARTUS® ProFLEX** torches can be used with many market-leading welding devices.

*The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.*

Technical details

Rating	125A DC 100A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4mm
Gas flow rate	7 - 20L/min

Liquid cooling floow	1.0 - 1.5L/min
Duty cycle	100%
Cooling type	liquid
Standard	225F [small consumables]
Length	4m
Control plug	2MAG - fit MAGNUM®