

Product details: TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6



product code: SPP250RA-4-mSRP1B-U-1BEZ

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

Product variants

| Index | Price |
|---|------------------------------|
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, SK35, 30cm hose, Rec6 SPP250RA-4-mSRP1B-U-1BEZ | €215.53 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP250RA-4-mSRP1B-U-1ESB | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to EWM® SPP250RA-4-mSRP1B-U-1EWM | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS® SPP250RA-4-mSRP1B-U-1FRO | €226.06 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPMPI® SPP250RA-4-mSRP1B-U-1KMP | €226.06 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to LINCOLN® SPP250RA-4-mSRP1B-U-1LIN | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP250RA-4-mSRP1B-U-1MAG | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to ESAB® SPP250RA-4-mSRP1B-U-2ESB | €273.47 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to FRONIUS® SPP250RA-4-mSRP1B-U-2FRO | €273.47 / pc Net price |

| Index | Price |
|---|-------------------------------------|
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to KEMPPI® SPP250RA-4-mSRP1B-U-2KMP | €273.47 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, control plug fit to MAGNUM® SPP250RA-4-mSRP1B-U-2MAG | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug SPP250RA-4-mSRP1B-U-8SPA | €222.11 / pc Net price |
| TIG 250R torch with SP9-90R rotary head, 4m, ProFLEX series, mini 1B, U package, SPARTUS® control plug SPP250RA-4-mSRP1B-U-9SPA | €222.11 / pc Net price |

Product description

SPARTUS® PROFLEX TIG 250R TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES

In the production of **SPARTUS® ProFLEX** torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In **SPARTUS® ProFLEX** holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.







textile-polyester cable
package cover



textile-rubber cable
package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

ROTATING TORCH HEADS

Rotating SPARTUS® torch heads are an excellent solution for work carried out in hard-to-reach places. The body of the burner, thanks to its construction, allows the head to be rotated 360°. This solution increases the comfort and efficiency of work. In addition, the rotating torch head system allows you to quickly replace the head, depending on your needs. In the SP250R holders, heads of standard SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, **SPARTUS® ProFLEX** torches can be used with many market-leading welding devices.

The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

| | |
|----------------------------|--|
| Rating | 125A DC 100A AC |
| Electrode diameter | 0.5, 1.0, 1.6, 2.0, 2.4 |
| Gas flow rate | 7 - 20 L/min |
| Liquid cooling flow | 1.0 - 1.5 L/min |
| Duty cycle | 100% |
| Cooling type | liquid |
| Standard | replaceable, rotary torch heads |
| Length | 4m |
| Control plug | SK35, 2m hose, 1/4 nut |