

Product details: TIG 18SC torch, 4m, ProFLEX series, 1B, U package, SK35, 30cm hose, Rec6

nov-weld



product code: **SPP18SC-4-SRP1B-U-1BEZ**

## POLISH PRODUCT

Torches **SPARTUS®** **ProFLEX** brand are made in Poland

### Product variants

| Index  | Price                            |
|--|----------------------------------|
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, SK35, 30cm hose, Rec6</b><br>SPP18SC-4-SRP1B-U-1BEZ        | <b>€234.81 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to ESAB®</b><br>SPP18SC-4-SRP1B-U-1ESB    | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to EWM®</b><br>SPP18SC-4-SRP1B-U-1EWM     | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to FRONIUS®</b><br>SPP18SC-4-SRP1B-U-1FRO | <b>€245.34 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to KEMPPi®</b><br>SPP18SC-4-SRP1B-U-1KMP  | <b>€245.34 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to LINCOLN®</b><br>SPP18SC-4-SRP1B-U-1LIN | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to MAGNUM®</b><br>SPP18SC-4-SRP1B-U-1MAG  | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to ESAB®</b><br>SPP18SC-4-SRP1B-U-2ESB    | <b>€292.74 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to FRONIUS®</b><br>SPP18SC-4-SRP1B-U-2FRO | <b>€292.74 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to KEMPPi®</b><br>SPP18SC-4-SRP1B-U-2KMP  | <b>€292.74 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, control plug fit to MAGNUM®</b><br>SPP18SC-4-SRP1B-U-2MAG  | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, SPARTUS® control plug</b><br>SPP18SC-4-SRP1B-U-8SPA        | <b>€241.39 / pc</b><br>Net price |
| <b>TIG 18SC torch, 4m, ProFLEX series, 1B, U package, SPARTUS® control plug</b><br>SPP18SC-4-SRP1B-U-9SPA        | <b>€241.39 / pc</b><br>Net price |

Hand torch TIG 18SC 4m, series SPARTUS Pro, 4B, package X, with connection SPARTUS®  
SPP18SC-4-SRP4B-X-9SPA

€255.12 / pc  
Net price

Hand torch TIG 18SC 8m, series SPARTUS Pro, 4B, package X, with connection SPARTUS®  
SPP18SC-8-SRP4B-X-9SPA

€295.56 / pc  
Net price

## Product description

# SPARTUS® PROFLEX TIG 18SC TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

### CABLES

In the production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

### CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.





textile-polyester cable  
package cover



textile-rubber cable  
package cover

## TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

## WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

*The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.*

## Technical details

|                            |   |
|----------------------------|---|
| <b>Rating</b>              | <b>280A AC 400A DC</b>                          |
| <b>Electrode diameter</b>  | <b>0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0, 4.8mm</b> |
| <b>Gas flow rate</b>       | <b>7 - 20 l/min</b>                             |
| <b>Liquid cooling flow</b> | <b>1.0 - 1.5 l/min</b>                          |
| <b>Duty cycle</b>          | <b>100%</b>                                     |
| <b>Cooling type</b>        | <b>liquid</b>                                   |
| <b>Standard</b>            | <b>18SC [large consumables]</b>                 |
| <b>Length</b>              | <b>4m</b>                                       |
| <b>Control plug</b>        | <b>SK35, 30cm hose, Rec6</b>                    |