

Product details: TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, SK35, 30cm hose, Rec6



product code: SPP155FA-4-SW1F-U-1BEZ

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

Product variants

Index	Price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, SK35, 30cm hose, Rec6 SPP155FA-4-SW1F-U-1BEZ	€220.23 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to ESAB® SPP155FA-4-SW1F-U-1ESB	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to EWM® SPP155FA-4-SW1F-U-1EWM	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to FALTIG® SPP155FA-4-SW1F-U-1FAL	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to FRONIUS® SPP155FA-4-SW1F-U-1FRO	€230.76 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to KEMPPI® SPP155FA-4-SW1F-U-1KMP	€230.76 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to LINCOLN® SPP155FA-4-SW1F-U-1LIN	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to MAGNUM® SPP155FA-4-SW1F-U-1MAG	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to ESAB® SPP155FA-4-SW1F-U-2ESB	€243.93 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to FRONIUS® SPP155FA-4-SW1F-U-2FRO	€278.16 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to KEMPPI® SPP155FA-4-SW1F-U-2KMP	€230.76 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, control plug fit to MAGNUM® SPP155FA-4-SW1F-U-2MAG	€226.81 / pc Net price

Index	Price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, SPARTUS® control plug SPP155FA-4-SW1F-U-8SPA	€226.81 / pc Net price
TIG 155F torch with SP9-70 head, 4m, ProFLEX series, 1F, U package, SPARTUS® control plug SPP155FA-4-SW1F-U-9SPA	€226.81 / pc Net price

Product description

SPARTUS® PROFLEX TIG 155F TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES



In
the



production of SPARTUS® ProFLEX torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable package cover



textile-rubber cable package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

REPLACEABLE TORCH HEADS

Replaceable SPARTUS® torch heads are an innovative solution that allows for instant replacement of the head, depending on the needs - size of the head, angle of inclination. In the SP155F holders, heads of the standard SP24/24W, SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	SP24 / SP9: 125A DC, 100A AC ; SP1726: 150A DC, 125A AC
Electrode diameter	SP24 / SP9: 0.5 - 2.4mm ; SP1726: 0.5 - 3.2mm
Gas flow rate	7 - 15 l/min
Duty cycle	80%
Cooling type	gas
Standard	9 [small consumables], replaceable torch heads
Length	4m
Control plug	SK35, 30cm hose, Rec6