

Product details: TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, SK35, 30cm hose, Rec6



product code: SPP150RA-4-mSRP1B-U-1BEZ

POLISH PRODUCT

Torches SPARTUS® ProFLEX brand are made in Poland

Product variants

Index	Price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, SK35, 30cm hose, Rec6 SPP150RA-4-mSRP1B-U-1BEZ	€191.49 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to ESAB® SPP150RA-4-mSRP1B-U-1ESB	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to EWM® SPP150RA-4-mSRP1B-U-1EWM	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to FALTIG® SPP150RA-4-mSRP1B-U-1FAL	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to FRONIUS® SPP150RA-4-mSRP1B-U-1FRO	€202.73 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to KEMPPI® SPP150RA-4-mSRP1B-U-1KMP	€202.73 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to LINCOLN® SPP150RA-4-mSRP1B-U-1LIN	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to MAGNUM® SPP150RA-4-mSRP1B-U-1MAG	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to ESAB® SPP150RA-4-mSRP1B-U-2ESB	€216.78 / pc Net price

Index	Price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to FRONIUS® SPP150RA-4-mSRP1B-U-2FRO	€253.30 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to KEMPPI® SPP150RA-4-mSRP1B-U-2KMP	€202.73 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, control plug fit to MAGNUM® SPP150RA-4-mSRP1B-U-2MAG	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, SPARTUS® control plug SPP150RA-4-mSRP1B-U-8SPA	€198.52 / pc Net price
TIG 150R torch with SP9-90R rotary head, 4m, ProFLEX series, 1B, U package, SPARTUS® control plug SPP150RA-4-mSRP1B-U-9SPA	€198.52 / pc Net price

Product description

SPARTUS® PROFLEX TIG 150R TORCH

SPARTUS® ProFLEX TIG torches manufactured in Poland are characterized by high quality of components used and solid workmanship. A wide selection of torch bodies, handles, microswitches and cable packages allows you to meet the expectations of even the most demanding welders.

CABLES

In the production of **SPARTUS® ProFLEX** torches, a professional cotton braided hose, made in the USA, was used. The high-density outer braid provides the highest level of flexibility, both at high and low temperatures.

CABLE PACKAGES

In SPARTUS® ProFLEX holders, 3 types of cable covers can be used. The „T” and „U” packages are manufactured in a textile-polyester cover, while the „X” package is made in a textile-rubber cover. The „U” and „X” packages also have a one-meter section of leather behind the handle.



textile-polyester cable
package cover



textile-rubber cable
package cover

TOOLBOX

SPARTUS® ProFLEX torches are equipped with a handy box containing consumables (toolbox).

ROTATING TORCH HEADS

Rotating SPARTUS® torch heads are an excellent solution for work carried out in hard-to-reach places. The body of the burner, thanks to its construction, allows the head to be rotated 360°. This solution increases the comfort and efficiency of work. In addition, the rotating torch head system allows you to quickly replace the head, depending on your needs. In the SP150R holders, heads of standard SP9/20 or SP17/18/26 can be used interchangeably.

WIDE CHOICE OF CONNECTIONS

Thanks to the wide range of connections, SPARTUS® ProFLEX torches can be used with many market-leading welding devices.

The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	125A DC 100A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4mm
Gas flow rate	7 - 15 l/min
Duty cycle	80%
Cooling type	gas
Standard	9 [small consumables], replaceable, rotary torch heads
Length	4m
Control plug	SK35, 30cm hose, Rec6