

Product details: TIG 26V torch, 4m, Easy series, control in the handle, package D, SK35, 30cm hose, Rec6



product code: **SPE26V-4-SRE1B-D-1BEZ**

## Product variants

### Index

---

**TIG 26V torch, 4m, Easy series, control in the handle, package D, SK35, 30cm hose, Rec6**  
**SPE26V-4-SRE1B-D-1BEZ**

---

**TIG 26V torch, 4m, Easy series, control in the handle, package D, SPARTUS® connection**  
**SPE26V-4-SRE1B-D-8SPA**

---

**TIG 26V torch, 4m, Easy series, control in the handle, package X, SK35, 30cm hose, Rec6**  
**SPE26V-4-SRE1B-X-1BEZ**

---

**TIG 26V torch, 4m, Easy series, control in the handle, package X, SPARTUS® connection**  
**SPE26V-4-SRE1B-X-8SPA**

---

## Product description

### SPARTUS® EASYTIG TORCH 26V with valve

The **SPARTUS® EasyTIG** series is a classic solution of welding torches designed with simplicity and ergonomics in mind.

## TORCH BODIES

The torch body equipped with a valve allows for smooth regulation of the gas stream depending on the specific requirements of the welder.

## HANDLES

Thanks to a handle with a single microswitch, dedicated to work with machines equipped with a control connector for contactless ignition.

## WIRE PACKAGE

For solutions with control in the handle, a cable package is available, marked with the D symbol, which is in a rubber. Package comes with a basic set of consumables.

## CONNECTIONS

A wide range of connections enables the use of SPARTUS® EasyTIG torches with a valve and control in the handle with the most popular welding devices available on the European market.

*The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.*



## Technical details

Rating	200A DC 150A AC
Electrode diameter	0.5 - 4.0mm
Gas flow rate	7 - 20 l/min
Duty cycle	35%
Cooling type	gas
Standard	26 [large consumables]
Length	4m
Control plug	SK35, 30cm hose, Rec6