Product details: FERROS 3D 1200 x 1200 x 200 octagonal with rotary positioner SPARTUS® 2000



product code: SP28C-12-12-RP2000



Completion date to be agreed with the sales manager

Product variants

Index

FERROS 3D 1200 x 1200 x 200 octagonal with rotary positioner SPARTUS® 2000 SP28C-12-12-RP2000

FERROS 3D 1200 x 1200 x 200 octagonal with rotary positioner SPARTUS® 1000 SP28C-12-12-RP1000

FERROS 3D 1200 x 1200 x 200 octagonal with rotary positioner SPARTUS \$ 5000 SP28C-12-12-RP5000

Product description

NOV-WELD Generate: 2025-08-24 1 / 5

INCREASE WORK EFFICIENCY THANKS TO MODERN SOLUTIONS!

FERROS

1200 x 1200 x 200mm (octagonal)



• CAST IRON ENGJL-300

For the casting of the countertop, high-strength cast iron EN-GJL-300 was used, which is characterized by high wear resistance.

• TABLE TOP 25MM

The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.

• MILLIMETRIC SCALE

The applied millimeter scale facilitates precise installation of the element during processing.

• 3D SIDE

It allows to expand the working surface and joining the table tops.

D28 SYSTEM

Drilled and chamfered holes 28mm.

SPARTUS® welding positioners with a countertop size of 1200 x 1200 x 200.



rotate the worktable with variable speed in both directions and change the angle of the main frame. Control is achieved through a foot pedal. The self-locking drive ensures that the rotating disc halts in any position. The positioner's mechanisms enable rotation around its own axis and deviation of the rotator up to 140° from the horizontal, while the tilt angle after mounting the tabletop is 90°. Control interface: manual panel + foot pedal (on separate cables).

The table with a positioner allows for adjusting the workstation position according to the worker's needs. The positioner provides the ability to

Advantages:

- rotating worktable (in both directions)
- tilt angle adjustment
- smooth speed adjustment
- intuitive and convenient control

ACCESSORY SETS

NOV-WELD Generate: 2025-08-24 2 / 5









Accessories SET 1 includes:

SP010-30-005 Angle Bracket 175x50x75mm hole/slot 8pcs SP010-50-002 Universal stopper 225x50x25mm 4 pcs SP010-70-001 180° mounting clamp with 300x300mm holder 6 pcs

SP010-60-001 Rapid locking bolt fi 28x50mm 22 pcs SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brusch fi 30x80mm 1 pc. SP010-90-001 Oilstone 200x50x25mm 1 pc. SP010-90-002 1I dispenser bottle 1 pc.

Accessories SET 2 includes:

 ${\tt SP010\text{-}30\text{-}005 \ Angle \ bracket \ 175x50x75mm \ hole/slot \ 2 \ pcs \ \ SP010\text{-}23\text{-}300R \ Angle \ bracket \ 275x100x300mm \ right \ 1 \ pc.}}$ SP010-50-002 Universal stopper 225x50x25mm 4 pcs $SP010-70-001\ 180^\circ\ mounting\ clamp\ with\ 300x300mm\ holder\ SP010-23-600R\ Angle\ bracket\ 375x100x600mm\ right\ 1\ pc.$

SP010-60-001 Rapid locking bolt fi 28x50mm 20 pcs SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brusch fi 30x80mm 1 pc. SP010-90-001 Olistone 200x50x25mm 1 pc. SP010-90-002 1I dispenser bottle 1 pc.

Accessories SET 3 includes:

SP010-23-600L Angle bracket 375x100x600mm left 1 pc. SP010-30-002 Angle bracket 175x50x175mm hole/slot 4 pcs SP010-30-005 Angle brecket 175x50x75mm hole/slot 4 pcs SP010-50-002 Universal stopper 225x50x25mm 6 pcs SP010-70-001 180° mounting clamp witch 300x300mm holder 10 pcs

SP010-60-001 Rapid locking bolt fi 28x50mm 22 pcs SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brush fi 30x80mm 1 pc. SP010-90-001 Olistone 200x50x25mm 1 pc. SP010-90-002 1I dispencer bottle 1 pc.













NOV-WELD Generate: 2025-08-24 3/5

Accessories SET 4 includes:

SP010-23-600L Angle bracket 375x100x600mm left 2 pcs SP010-23-600R Angle bracket 375x100x600mm right 2 pcs SP010-23-300R Angle bracket 275x100x300mm right 1 pc. SP010-30-005 Angle bracket 175x50x75 hole/slot 4 pcs SP010-30-013 Angle bracket 175x50x275mm hole/slot 6 pcs SP010-23-600R Angle bracket 375x100x600mm right 1 pc. SP010-50-002 Universal stopper 225x50x25mm 4 pcs SP010-65-001A Prysm fi 60 90° 4 pcs

SP010-60-001 Rapid locking bolt fi 28x50mm 28 pcs

SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brusch fi 30x80mm 1 pc. SP010-90-001 Oilstone 200x50x25mm 1 pc. SP010-90-002 1I dispenser bottle 1 pc.

Accessories SET 5 includes:

SP010-23-300L Angle bracket 275x100x300mm left 1 pc. SP010-23-600L Angle bracket 375x100x600mm left 1 pc. SP010-23-800L Angle bracket 375x100x800mm left 1 pc. SP010-23-800R Angle bracket 375x100x800mm right 1 pc. SP010-30-005 Angle bracket 175x50x75 hole/slot 4 pcs SP010-50-002 Universal stopper 225x50x25mm 6 pcs $SP010-50-014\ Universal\ stop\ 500x100x25mm\ hole/slot\ 4\ pcs\ SP010-50-002\ Universal\ stopper\ 225x50x25mm\ 8\ pcs$ 12 ncs

SP010-60-001 Rapid locking bolt fi 28x50mm 40 pcs SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brusch fi 30x80mm 1 pc. SP010-90-001 Oilstone 200x50x25mm 1 pc. SP010-90-002 1I dispenser bottle 1 pc.

Accessories SET 6 includes:

SP010-20-050 U-shape block 500x200x200mm 2 pcs SP010-20-100 U-shape block 1000x200x200mm 2 pcs SP010-23-300L Angle bracket 275x100x300mm left 2 pcs SP010-23-300R Angle bracket 275x100x300mm right 2 pcs SP010-23-600L Angle bracket 375x100x600mm left 2 pcs SP010-23-600R Angle bracket 375x100x600mm right 2 pcs SP010-70-001 180° mounting clamp with 300x300mm holder SP010-30-002 Angel bracket 175x50x175mm hole/slot 6 pcs SP010-30-002 Angle bracket 175x50x175mm hole/slot 8 pcs SP010-30-005 Angle bracket 175x50x75mm hole/slot 8 pcs SP010-30-013 Angle bracket 175x50x275mm hole/slot 4 pcs $\ensuremath{\,\mathsf{SP010\text{-}}70\text{-}001}$ 180° mounting clamp with 300x300mm holder 20 pcs SP010-60-001 Rapid locking bolt fi 28x50mm 46 pcs SP010-90-003A Hexagon allen wrench 150mm 1 pc. SP010-90-004 Nylon brusch fi 30x80mm 1 pc. SP010-90-001 Oilstone 200x50x25mm 1 pc. SP010-90-002 1I dispenser bottle 1 pc.

NOV-WELD Generate: 2025-08-24 4/5

Technical details

Size of the work surface	1200 x 1200 x 200mm
Made	casted
Material	EN-GJL-300 cast iron acc. to EN 1561
Table top thickness	25mm
Table horizontal precision	0.1/1000mm
Table vertical precision	0.1/200mm
Standard	D28 (drilled and milled holes 28mm diameter)
Supporting structure	Positioner
Carrying capacity	2000kg/positioner
Carrying capacity with tabletop	1520kg
Table top weight	480kg
Input	~3× 400V ± 10% 50 / 60 Hz

NOV-WELD Generate: 2025-08-24 5 / 5