



product code: **SP030-00-554**
product ean: **5900391249390**

Standard Equipment:

- extraction arm
- support bracket
- fan
- wall-mounted switch with safety features



Additional Paid Options:

- LED lighting in the suction nozzle
- automatic operation sensor for welding

processes

Execution of the contract - 4 weeks

Made in EU

Product variants

| Index | Price |
|---|------------------------------------|
| AeroClean 1600 4m welding fume extractor SP030-00-554 | €1,926.19 / pc Net price |
| AeroClean 1600 2m welding fume extractor SP030-00-552 | €1,840.48 / pc Net price |
| AeroClean 1600 3m welding fume extractor SP030-00-553 | €1,878.57 / pc Net price |

Product description

SPARTUS® AeroClean welding fume extractor

SPARTUS® AeroClean welding fume extractor units are advanced systems designed to remove light air contaminants during welding tasks that require continuous operation of the extraction system. Thanks to its universal design, **SPARTUS® AeroClean** is the perfect solution for a wide range of applications in various work environments.

- **Universal Design:** AeroClean extraction units are designed to adapt to a variety of needs and working conditions.
- **External Joints:** All joints are located on the exterior, minimizing airflow resistance and ensuring efficient contaminant extraction.
- **Low Flow Resistance:** The device's design guarantees smooth airflow, which translates to effective extraction performance and minimizes energy consumption.
- **Easy Maintenance:** The interior of the pipes is smooth and easy to keep clean, ensuring the long-lasting and trouble-free operation of the device.



SPARTUS® AeroClean is a reliable partner in providing a clean and safe working environment, protecting workers from harmful substances released during welding. Thanks to innovative technological solutions, **AeroClean** ensures the highest quality of extraction, which translates into efficiency and comfort at work.

Applications:

- Welding tasks that require continuous operation of the extraction system
- Removal of light air contaminants
- Protecting workers' health and improving working conditions

Technical details

| | |
|----------------------|----------------------------------|
| Model | - |
| Reach | 4m |
| Diameter | 160mm |
| Nozzle | 315mm |
| Rotation axes | 1 |
| Ventilator | T075 |
| Flow | 1000m³/h |
| Noise level | 77dB(A) |
| Power | 0,75kW |
| Input | ~3× 400V ± 10% 50 / 60 Hz |