



product code: **SP030-03-101**
product ean: **5900391249413**

Standard Equipment:

- extraction arm
- support bracket
- fan
- wall-mounted switch with safety features



Additional Paid Options:

- LED lighting in the suction nozzle
- automatic operation sensor for welding

processes

Execution of the contract - 2 weeks

Made in EU

Product variants

Index	Price
AeroClean 2000 3m welding fume extractor SP030-03-101	€2,251.98 / pc Net price
AeroClean 2000 2m welding fume extractor SP030-03-100	€2,185.02 / pc Net price
AeroClean 2000 4m welding fume extractor SP030-03-102	€2,318.94 / pc Net price

Product description

SPARTUS® AeroClean welding fume extractor

SPARTUS® AeroClean welding fume extractor units are advanced systems designed to remove light air contaminants during welding tasks that require continuous operation of the extraction system. Thanks to its universal design, **SPARTUS® AeroClean** is the perfect solution for a wide range of applications in various work environments.

- **Universal Design:** AeroClean extraction units are designed to adapt to a variety of needs and working conditions.
- **External Joints:** All joints are located on the exterior, minimizing airflow resistance and ensuring efficient contaminant extraction.
- **Low Flow Resistance:** The device's design guarantees smooth airflow, which translates to effective extraction performance and minimizes energy consumption.
- **Easy Maintenance:** The interior of the pipes is smooth and easy to keep clean, ensuring the long-lasting and trouble-free operation of the device.



SPARTUS® AeroClean is a reliable partner in providing a clean and safe working environment, protecting workers from harmful substances released during welding. Thanks to innovative technological solutions, **AeroClean** ensures the highest quality of extraction, which translates into efficiency and comfort at work.

Applications:

- Welding tasks that require continuous operation of the extraction system
- Removal of light air contaminants
- Protecting workers' health and improving working conditions

Technical details

Model	-
Reach	3m
Diameter	200mm
Nozzle	350mm
Rotation axes	1
Ventilator	T220
Flow	2000m³/h
Noise level	80dB(A)
Power	2,2kW
Input	~3× 400V ± 10% 50 / 60 Hz