



product code: **SP030-05-002**
product ean: **5900391249499**

Standard equipment:

- Vortex Eco 160 extraction arm 2m
- AirMaster mobile air ventilation system



Additional paid options:

- EC motor

Order fulfillment time - 2 weeks

Made in EU

Product variants

| Index | Price |
|---|------------------------------------|
| Mobile welding fume extractor AirMaster 2m SP030-05-002 | €2,702.82 / pc Net price |
| Mobile welding fume extractor AirMaster 3m SP030-05-003 | €2,740.77 / pc Net price |
| Mobile welding fume extractor AirMaster Duo 2m SP030-05-302 | €3,178.22 / pc Net price |
| Mobile welding fume extractor AirMaster Duo 3m SP030-05-303 | €3,254.10 / pc Net price |

Product description

Mobile Welding Fume Extractors SPARTUS® AirMaster

AirMaster is a mobile air filtration system designed to remove dust and fumes that often occur during welding processes. By utilizing the Vortex Eco extraction arm, the device allows for the effective elimination of contaminants directly at their source. The **AirMaster** filter components include a metal pre-filter and a modular main cartridge that can be easily replaced.

- **Dual filtration:** Two stages of filtration effectively eliminate contaminants from the air.
- **High performance:** Filtration capacity up to 1400 m³/h ensures efficient air cleaning.
- **Full mobility:** The housing equipped with wheels (including two swivel wheels) ensures ease of movement.
- **Filter contamination indicator:** Allows for quick determination of when the filter needs cleaning or replacement.
- **Easy maintenance:** Simple access to filter cartridges facilitates their replacement and maintenance.



Applications:

- Welding work that does not require continuous extraction
- Work at repair stations
- Local ventilation (except for corrosive and aggressively acting fumes or chemical gases)
- Removal of light air pollutants
- Protecting workers' health and improving working conditions

Technical details

| | |
|--------------------|----------------------------------|
| Model | - |
| Reach | 2m |
| Flow | 1400 m³/h |
| Noise level | 74 dB(A) |
| Power | 1,1 kW |
| Input | ~1× 230V ± 10% 50 / 60 Hz |