



product code: **SP030-06-003**
product ean: **5900391249543**

Standard equipment:

- Vortex 160 extraction arm 3m
- ClearStream 1000 mobile air ventilation system



Additional paid options:

- HEPA filter
- EC motor

Order fulfillment time - 2 weeks

Made in EU

Product variants

| Index | Price |
|--|------------------------------------|
| Mobile welding fume extractor ClearStream 1000 3m SP030-06-003 | €4,218.28 / pc Net price |
| Mobile welding fume extractor ClearStream 1000 2m SP030-06-002 | €4,184.80 / pc Net price |
| Mobile welding fume extractor ClearStream 2000 2m SP030-06-202 | €5,932.37 / pc Net price |
| Mobile welding fume extractor ClearStream 2000 3m SP030-06-203 | €5,994.87 / pc Net price |
| Mobile welding fume extractor ClearStream Duo 2000 2m SP030-06-302 | €6,434.55 / pc Net price |
| Mobile welding fume extractor ClearStream Duo 2000 3m SP030-06-303 | €6,501.51 / pc Net price |


Product description

Mobile Welding Fume Extractors SPARTUS® ClearStream 1000

ClearStream 1000 is designed for effective filtering of dust generated by activities such as welding, grinding, cutting, and processing of plastics and metals. This model utilizes an advanced, three-stage filtration system. Preliminary cleaning is done using a metal filter that captures larger particles and sparks. Next, the main cartridge filter thoroughly removes minor contaminants. Final cleaning is provided by activated carbon-coated fabric. **ClearStream 1000** is equipped with a manual system for cleaning the main filter using compressed air (it has its own 10-liter tank), which increases its

efficiency and extends its lifespan. The device is recommended for applications requiring continuous air quality control.

- **Advanced filtration:** Utilizes a three-stage filtration process, ensuring effective removal of various air contaminants.
- **High performance:** Filtration capacity of 1000 m³/h ensures efficient air cleaning.
- **Full mobility:** The housing equipped with wheels (including two swivel wheels) ensures easy movement.
- **Easy filter cartridge handling:** The design provides easy access and handling of the filters, facilitating their regular cleaning and maintenance.



Applications:

- Welding work requiring continuous extraction
- Work at repair stations
- Local ventilation (excluding corrosive and aggressively acting fumes or chemical gases)
- Professional use
- Protecting employees' health and improving working conditions

Technical details

| | |
|--------------------|----------------------------------|
| Model | - |
| Reach | 3m |
| Flow | 1000 m³/h |
| Noise level | 72 dB(A) |
| Power | 1,1 kW |
| Input | ~3× 400V ± 10% 50 / 60 Hz |