

product code: **M-308LSI-08-S200**  
product ean: **5900391250808**



**Standards:**

EN 13479  
EN ISO 14343-A-G 19 9 LSi  
AWS A5.9 / ASME SFA5.9 ER 308LSi

**Approvals:** TÜV, DB

## Product variants

Index	Price
<b>Welding wire ER308LSi D200 5kg 0.8mm</b> M-308LSI-08-S200	<b>€28.00 / pc</b> Net price
<b>Welding wire ER308LSi D100 1kg 0.8mm</b> M-308LSI-08-S100	<b>€6.43 / pc</b> Net price
<b>Welding wire ER308LSi D300 15kg 0.8mm</b> M-308LSI-08-B300	<b>€84.02 / pc</b> Net price

## Product description

### SPARTUS® ER308LSi welding wire

SPARTUS® ER308LSi is a premium-quality welding wire made from low-carbon stainless steel. It is design for MIG welding of austenitic steels such as AISI 301, 302, 304, 304L, 308, and 308L, as well as 18% Cr / 8% Ni steels.

Key features:

- **Superior corrosion resistance** – ensures durable, long-lasting welds, even in harsh environments.
- **Excellent mechanical properties** – provides high strength and reliability for critical applications.
- **Intergranular corrosion resistance** – protects welds from degradation when exposed to various liquid media.

Applications:

- **Pipeline construction** – reliable performance in welding pipeline components.
- **Tank production and structural fabrication** – ideal for manufacturing high-precision plates, tanks, and other stainless steel structures.
- **General industrial use** – perfect for applications requiring high corrosion resistance.



# Technical details

<b>Intended Use</b>	<b>stainless steel</b>
<b>Type</b>	<b>ER308LSi</b>
<b>Wire diameter</b>	<b>0.8mm</b>
<b>Welding wire spool</b>	<b>≤ 5kg / Ø200mm</b>
<b>Weight</b>	<b>5kg</b>