

product code: 050-06-080HP
product ean: 5900391251430



High-Performance rotary burrs are designed to meet the most demanding applications in the machining industry. Thanks to the TiAlN coating, HP rotary burrs are highly resistant to high temperatures and oxidation. This coating provides the rotary burrs with exceptional hardness. These rotary burrs are especially recommended for use with hard steel alloys.

Product variants

Index

- Ball nosed cone rotary burr 8x20x6/45 HP
050-06-080HP
- Ball nosed cone rotary burr 6x16x6/50 HP
050-06-060HP
- Ball nosed cone rotary burr 14° 8x22x6/69
050-06-080
- Ball nosed cone rotary burr 10x25x6/50 HP
050-06-100HP
- Ball nosed cone rotary burr 14° 12,7x27x6/74
050-06-127
- Ball nosed cone rotary burr - long 14° 12x32x6/180
050-06-127-175
- Ball nosed cone rotary burr 12,7x32x6/65 HP
050-06-127HP
- Ball nosed cone rotary burr 14° 16x30x6/77
050-06-160
- Ball nosed cone rotary burr 14° 12x32x8/70
050-08-127
- Ball nosed cone rotary burr 14° 16x33x8/70
050-08-160

Technical details

Type	zaokrąglony stożkowy
Diameter of the working part (D1)	8mm

The length of the working part (L2)	20mm
Total length (L1)	45mm
Pivot diameter (D2)	6mm
Use	for general use (especially for hard metal steel alloys)