



product code: SP050-50-33K

Standard:

DIN EN 12254:2012-4
DIN EN 12254:2010 + AC:2011
EN 60825-4:2006

Protection class:

D AB7 + I AB8 + R AB6 + M AB8Y GDLS>1050-1400 nm, 280 mW/m² (>1050-1400, 100sec)

Product variants

Index	Price
3360x3300 laser welding cell	€4,821.40 / set
SP050-50-33K	VAT 23% €5,930.32 / set
4460x4400 laser welding cell	€6,339.26 / set
SP050-50-44K	VAT 23% €7,797.29 / set
5560x5500 laser welding cell	€7,886.88 / set
SP050-50-55K	VAT 23% €9,700.86 / set

Product description

SPARTUS® **PROTECT** - READY-TO-USE LASER WELDING CELL ENCLOSURE (CLASS 4)

SAFETY. FUNCTIONALITY. COMPLIANCE.

The complete SPARTUS® PROTECT protective enclosure is a ready-made solution designed specifically for laser class 4 workstations. With dimensions of 3360×3300 mm and a height of 2000 mm, it allows for the quick and safe creation of a dedicated work zone, providing optical protection in accordance with current safety standards. It is an ideal choice for companies looking for a professional, ready-to-use enclosure without the need to design a custom structure.

HIGH STANDARD OF OPTICAL PROTECTION

The **SPARTUS® PROTECT** enclosure is made from certified protective materials compliant with **DIN EN 12254:2012-4** and **EN 60825-4:2006** standards. It provides effective protection against laser radiation in the 1050-1400 nm wavelength range, with the following protection levels: D AB7 + I AB8 + R AB6 + M AB8Y GDLS>1050-1400 nm, 280 mW/m² (>1050-1400, 100 sec).

This ensures full safety even when working with the most demanding laser sources.

STABLE STRUCTURE WITH MOBILE ELEMENTS

Although it is a complete cell, the **SPARTUS® PROTECT** system retains its mobility. Each protective panel is equipped with swivel casters with locks, allowing for easy repositioning or configuration adjustment within the workspace. The

NOV-WELD Generate: 2025-06-01 1/2

structure combines stability with flexibility to adapt to changing production needs.

DOOR WITH VIEWING WINDOW - EASY ACCESS AND VISUAL MONITORING

The enclosure includes a door with an integrated protective viewing window. It allows for easy entry and exit from the work zone without compromising the integrity of the protective structure. The viewing panel ensures safe observation of internal processes without exposure to laser radiation. This feature is especially valuable in environments where



APPLICATIONS

The SPARTUS® PROTECT cell is suitable for any setting where effective protection against laser radiation is critical:

- laser welding and cutting workstations,
- research laboratories,
- precision industry production lines,

continuous process monitoring is essential.

• designated safety zones in industrial facilities.

SPARTUS® PROTECT - READY-MADE ENCLOSURE FOR SAFE LASER OPERATIONS

Invest in a proven, complete protective solution. **SPARTUS**® **PROTECT** is a ready-to-use cell that combines regulatory compliance, practical functionality, and the highest level of workplace safety.

NOV-WELD Generate: 2025-06-01 2 / 2