



## Product variants

### Index

**MAXIMUS 3D mobile lift welding table 3000 x 1500 (electrohydraulic version)**  
**SP28N-30-15-PE**

## Product description

### GUARANTEE YOURSELF CONSTANT SUPPORT WITH MAXIMUS TABLES!

- **S355J2+N NITREDED STEEL**  
S355J2+N steel grade used to make the welding table gives high strength, impact and scratch resistance, whereas plasma nitrided welded top significantly enhances protection against corrosion and weld spatter.
- **25mm TABLE TOP**  
The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.
- **MILLIMETRIC SCALE**  
The applied millimeter scale facilitates precise assembly of the element to be processed.
- **D28 SYSTEM**  
Drilled and chamfered holes 28mm.



**The use of SPARTUS mobile lift welding tables brings many benefits that translate into more effective and comfortable work.**



- **HEIGHT PRECISE ADJUSTMENT**

Setting the table top at the right customised height enhances the level of comfort during the performance of lengthy tasks, which has a significant impact on the work efficiency and welding quality. The working height of the lift (without the table top) is adjustable in the range from **450mm to 1000mm**.



- **LIFT CAPACITY**

Lifting system with a **high capacity of maximum 3500kg** (without the table top) allows you to load the unit with large-size elements and apply accessories to facilitate element assembly.

- **SAFETY**

The mobile lift is equipped with two protections:

- **maintenance interlocking system**



- **limit switch** - crushing protection



The **SPARTUS mobile lift welding tables** is a modern and convenient solution for professionals who value solid solutions that facilitate the work of welders.

## Technical details

Size of the work surface	3000 x 1500 x 200mm
Made	welded with a protective coating (nitrided)
Material	S355J2+N steel acc. to EN 10025-2
Table top thickness	25mm
Table horizontal precision	0.3/1000mm
Table vertical precision	0.3/200mm
Standard	D28 (drilled and milled holes 28mm diameter)
Supporting structure	Table lift
Nominal capacity (table top + details)	3500kg
Carrying capacity with tabletop	2000kg
Total table height	650 - 1200mm
Lifting	electro-hydraulic
Lifting speed	30mm/s
Lowering speed	40mm/s

Maximum number of lifting cycles	10/h
Table top weight	1500 kg
Input	~3× 400V ± 10% 50 / 60 Hz