

Product details: TIG torch 26, 4m, Easy series, 1B, package X, SK35, 30cm hose, Rec6

nov-Weld

SP26 EASY

product code: SPE26-4-SRE1B-X-1BEZ
product ean: 5900391248973



Product variants

Index	Price
TIG torch 26, 4m, Easy series, 1B, package X, SK35, 30cm hose, Rec6 SPE26-4-SRE1B-X-1BEZ	€69.75 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to ESAB® SPE26-4-SRE1B-X-1ESB	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to EWM® SPE26-4-SRE1B-X-1EWM	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to FALTIG® SPE26-4-SRE1B-X-1FAL	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to FRONIUS® SPE26-4-SRE1B-X-1FRO	€78.76 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to KEMPPi® SPE26-4-SRE1B-X-1KMP	€78.76 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to LINCOLN® SPE26-4-SRE1B-X-1LIN	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to MAGNUM® SPE26-4-SRE1B-X-1MAG	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to ESAB® SPE26-4-SRE1B-X-2ESB	€90.03 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to FRONIUS® SPE26-4-SRE1B-X-2FRO	€119.32 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to KEMPPi® SPE26-4-SRE1B-X-2KMP	€78.76 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, control plug fit to MAGNUM® SPE26-4-SRE1B-X-2MAG	€75.38 / pc Net price
TIG torch 26, 4m, Easy series, 1B, package X, SPARTUS® control plug SPE26-4-SRE1B-X-8SPA	€75.38 / pc Net price

TIG torch 26, 4m, Easy series, 1B, package X, SPARTUS® control plug
SPE26-4-SRE1B-X-9SPA

€75.38 / pc
Net price

Product description

SPARTUS® EASYTIG 26 TORCH

The **SPARTUS® EasyTIG** series is a classic solution of welding torches designed with simplicity and ergonomics in mind.

TORCH BODIES

Easy series torches are offered with a standard torch body (or a flexible version available in the configurator).

HANDLES

The handle used in the **SPARTUS® Easy** holder, thanks to its ergonomic design and non-slip lining, provides comfort and a high level of control, necessary for precise guidance of the torch.

WIRE PACKAGE

In **EasyTIG** torches, the set of cables, marked with the X symbol, is in a textile-rubber sheath with a section of leather behind the handle and a basic set of consumables.

CONNECTIONS

A wide range of connections enables the use of SPARTUS® torches with the most popular welding devices available on the European market.



The picture of the handle presented in the article is illustrative and depends on the options selected in the configurator and related products.

Technical details

Rating	200A DC 150A AC
Electrode diameter	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0mm
Gas flow rate	7 - 20 l/min
Duty cycle	35%
Cooling type	gas
Standard	26 [large consumables]
Length	4m
Control plug	SK35, 30cm hose, Rec6