



product code: SPE9-4-mSRE1B-X-1LIN

## Product variants

### Index

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to LINCOLN®**

SPE9-4-mSRE1B-X-1LIN

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, SK35, 30cm hose, Rec6**

SPE9-4-mSRE1B-X-1BEZ

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, SPARTUS® control plug**

SPE9-4-mSRE1B-X-8SPA

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, SPARTUS® control plug**

SPE9-4-mSRE1B-X-9SPA

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to KEMPPİ®**

SPE9-4-mSRE1B-X-1KMP

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to KEMPPİ®**

SPE9-4-mSRE1B-X-2KMP

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to FALTIG®**

SPE9-4-mSRE1B-X-1FAL

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to FRONIUS®**

SPE9-4-mSRE1B-X-1FRO

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to FRONIUS®**

SPE9-4-mSRE1B-X-2FRO

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to ESAB®**

SPE9-4-mSRE1B-X-1ESB

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to ESAB®**

SPE9-4-mSRE1B-X-2ESB

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to MAGNUM®**

SPE9-4-mSRE1B-X-1MAG

---

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to MAGNUM®**

SPE9-4-mSRE1B-X-2MAG

**TIG torch 9, 4m, Easy series, mini 1B, package X, control plug fit to EWM®**

SPE9-4-mSRE1B-X-1EWM

## Technical details

Rating	<b>125A DC 100A AC</b>
Electrode diameter	<b>0.5, 1.0, 1.6, 2.0, 2.4mm</b>
Gas flow rate	<b>7 - 15 l/min</b>
Duty cycle	<b>35%</b>
Cooling type	<b>gas</b>
Standard	<b>9 [small consumables]</b>
Length	<b>4m</b>
Control plug	<b>1LIN - fit LINCOLN®</b>