



product code: **EASYMIG270-PAK-24-3**
product ean: **5900391242445**

Package equipment:

- EasyMIG 270
- **MIG gun SPARTUS® SPE 240 3m**
- 2 x wire guide roller 0.8 - 1.0V fi30, additionally 2 x wire guide roller 1.0-1.2V fi30
- Electrode holder
- Work Clamp
- Gas hose
- User's manual

Product variants

Index	Price
EasyMIG 270 package EASYMIG270-PAK-24-3	€797.38 / pc Net price

Product description

SYNERGIC IGBT COMPACT

SPARTUS® EasyMIG 270 is modern, inverter and professional MIG/MAG welding machine with inert or active gas shielding and MMA coated electrode welding. SPARTUS® EasyMIG 270 is powered by 400V three-phase.

The maximum welding current for SPARTUS® EasyMIG 270 is 250A for MIG/MAG and 230A for MMA. 60% high working cycle ensures stable output parameters during long-term welding work.

SPARTUS® EasyMIG 270 is equipped in the **synergy system for MIG/MAG welding** with the ability to manually change parameters. You can choose the following programs: CO2 steel, mixed steel, core wire welding. Making the synergy correction is signalled by flashing LED on the machine's panel.

SPARTUS® EasyMIG 270 has a set of features supporting the welding process: **2T/4T work mode, inductance regulation, Arc Force, Hot Start** and **VRD**.

Professional four-roller feeder ensures stable welding wire feed. Resistant, robust and compact design makes it perfect equipment for difficult conditions, and there is a possibility of mounting a technical gas cylinder on the chassis of the machine.

SPARTUS® EasyMIG 270 is a compact machine designed mostly for efficient welding of steel constructions and working in difficult workshop conditions.

Technical details

Input	~3× 400V ± 10% 50 / 60 Hz
MIG welding current	50 - 250A
MIG duty cycle	60%

Output working voltage	16.5 - 26.5V
Wire feeder	built-in, 4-roll gear
Wire feeding speed	2 - 15m/min
Welding wire spool	≤ 15kg / Ø200/300mm
Wire diameter	0.8, 1.0, 1.2mm
Synergy	yes
2T/4T Control	yes
Additional MIG functions	inductance control, wire test, change polarity
TIG Lift	yes
TIG welding current	10 - 250A
MMA welding current	10 - 220A
Arc Force	yes
Hot Start	yes
VRD	yes
Current consumpition	13A
Power factor (cosφ)	0.93
Efficiency η	85%
Insulation class	F
Protection class	IP21
Weight	38kg
Dimensions	920 x 470 x 740mm