



product code: **PROCUT45PFC-PAK-45H-6**  
product ean: **5900391250693**

**Package equipped:** • ProCUT 45PFC • Plasma torch SPARTUS® 45H 6m • With toolbox (free consumables kit) • Built-in air filter with the pressure control • 3m work clamp • Gas hose • User's manual

\* used with retaining cap - 6 holes (60389)

## Product variants

Index	Price
<b>ProCUT 45PFC package</b> PROCUT45PFC-PAK-45H-6	<b>€884.56 / pc</b> Net price

## Product description

### A MODERN AND LIGHT PLASMA CUTTER

**SPARTUS® ProCUT 45PFC** is an inverter plasma cutter with integrated CNC control socket. Designed for cutting metals and other electrically conductive materials. It is powered with one-phase 230V source power. Through the use of modern technology, we have obtained excellent source with maximum cutting current 40A. The maximum thickness of cut material is 25mm.

Built-in system of contactless pilot arc ignition without HF – provides excellent quality of cutting edge and longer life of consumables. The easy-to-use panel with an LCD display allows for smooth adjustment of the cutting current and setting the appropriate pressure. In addition, the cutter is equipped with a 2T / 4T mode selector switch.

**SPARTUS® ProCUT 45PFC** is professional plasma cutter that will find application in manufacturing sectors, industry and as source of CNC plasma tables.

## Technical details

Input	~1× 230V ± 10% 50 / 60 Hz
Cutting current	20 - 40A
Max. cutting thickness	25mm
Duty cycle	60%
Output working voltage	18V
Recommended work pressure	5bar
Air consumption	150l/min
Gas post flow	yes
Pilot arc ignition	without HF
Current consumpton	19.7A

---

<b>Power factor (cosφ)</b>	<b>0.7</b>
<b>Insulation class</b>	<b>H</b>
<b>Protection class</b>	<b>IP21S</b>
<b>Weight</b>	<b>14kg</b>
<b>Dimensions</b>	<b>600 x 215 x 405mm</b>

---