

product code: SP15BT-2150-8



Product variants

Index

SPARTUS® screw compressor with a tank [2150/500 15kW 400V 8bar]
SP15BT-2150-8

SPARTUS® screw compressor with a tank [450/270 4kW 400V 10bar]
SP4BT-450-10

SPARTUS® screw compressor with a tank [550/270 4kW 400V 8bar]
SP4BT-550-8

SPARTUS® screw compressor with a tank [700/270 5.5kW 400V 10bar]
SP5.5BT-700-10

SPARTUS® screw compressor with a tank [800/270 5.5kW 400V 8bar]
SP5.5BT-800-8

SPARTUS® screw compressor with a tank [1000/270 7.5kW 400V 10bar]
SP7.5BT-1000-10

SPARTUS® screw compressor with a tank [1150/270 7.5kW 400V 8bar]
SP7.5BT-1150-8

SPARTUS® screw compressor with a tank [1400/500 15kW 400V 15bar]
SP15BT-1400-15

SPARTUS® screw compressor with a tank [1900/500 15kW 400V 10bar]
SP15BT-1900-10

Product description

Advantages of the device:

- reliable screw airends by global manufacturers (GHH RAND) designed for continuous operation,
- asymmetric design rotor's profiles to generate maximum power and performance at minimum energy cost,
- low-noise operation (67 dB),
- belt drive enabling easy modification of performance and maximum pressure by changing the pulley ratios,
- simplified access to maintain the airend,
- microprocessor controller with idle run function,

- a tank dedicated to the compressor power, with a capacity of 270 or 500l, ensuring uninterrupted transmission of the medium to the installation.

Technical details

Pressure	8bar
Capacity	2150l/min
Power	15kW
Drive	belt
Loudness	67dB
Plug	3/4"
Weight	520kg
Dimensions	1930x810x1760mm
Tank	500l