



product code: **080-10-430XT**  
product ean: **5900391001028**

## Product variants

Index	Price
<b>Helmet SPARTUS® Pro 430XT with true color filter</b> 080-10-430XT	<b>€82.67 / pc</b> Net price
<b>Helmet SPARTUS® Pro 430XT with true color filter, hard hat and adapter</b> 080-10-430XTK	<b>€115.58 / pc</b> Net price

## Product description

The **SPARTUS® Pro 430XT** welding helmet is designed to protect the welder's eyes and face from harmful radiation and welding spatters. It is perfect for MIG / MAG, TIG and MMA welding. Additionally, it also has a grinding option.

The Pro 430XT welding helmet has an automatic filter with the **highest optical class 1/1/1/1** and a **very large field of view of 100x73mm**. Fast lens reaction time - 1/30,000s is guaranteed thanks to the use of 4 very sensitive sensors, which is an important factor while welding with low currents. The preview of the view is presented in real colors (**true color**).

The filter enables **smooth adjustment of the darkness level** (DIN 4 -8 / DIN 9-13), sensitivity and delay time. The GRIND switch activates the grinding function. The filter is powered by solar cells and a replaceable battery. The "TEST" button on the internal panel allows you to check the correct functionality of the filter.

The SPARTUS® Pro 430XT welding helmet is made of durable and light material. The multi-stage adjustment of the headgear allows not only a perfect fit, but also the right distance between the filter and the welder's eyes. The large field of view and comfort of work allows to obtain a high quality weld. The product is intended for the most demanding welders.

## Technical details

Usage	<b>MIG/MAG, TIG, MMA arc welding</b>
Active field of view	<b>100 x 73mm</b>
Filter size	<b>122 x 125 x 9mm</b>
Filter optical class	<b>1 / 1 / 1 / 1</b>
Sensors	<b>4</b>
Shading (standby)	<b>DIN 3.5</b>
Variable welding shades (operating)	<b>DIN 4 - 8 or DIN 9 - 13</b>

---

<b>UV/IR protection degree</b>	<b>to DIN16</b>
<b>Light to dark switching time</b>	<b>1/30 000s</b>
<b>Delay control of light to dark switching time</b>	<b>0.25 - 0.85s</b>
<b>Power supply</b>	<b>solar cells and lithium battery</b>
<b>Grinding</b>	<b>yes</b>
<b>Adjustment knob and switch</b>	<b>inside</b>
<b>Weight</b>	<b>500g</b>

---