



product code: **SP020-00-150**  
product ean: **5900391244142**

Order fulfillment time: 6 weeks.

► **MADE IN EU**

## Product variants

| Index   | Price                               |
|---|-------------------------------------|
| <b>Welding positioner SPARTUS® 150</b><br>SP020-00-150  | <b>€3,972.77 / pc</b><br>Net price  |
| <b>Welding positioner SPARTUS® 100</b><br>SP020-00-100  | <b>€2,282.48 / pc</b><br>Net price  |
| <b>Welding positioner SPARTUS® 300</b><br>SP020-00-300  | <b>€7,067.66 / pc</b><br>Net price  |
| <b>Welding positioner SPARTUS® 500</b><br>SP020-00-500  | <b>€8,317.52 / pc</b><br>Net price  |
| <b>Welding positioner SPARTUS® 1000</b><br>SP020-01-000 | <b>€10,460.14 / pc</b><br>Net price |
| <b>Welding positioner SPARTUS® 2000</b><br>SP020-02-000 | <b>€14,031.17 / pc</b><br>Net price |
| <b>Welding positioner SPARTUS® 5000</b><br>SP020-05-000 | <b>€26,633.93 / pc</b><br>Net price |

## Product description

The welding positioner SPARTUS® 150 is characterized by a compact design ensuring excellent access to the workpiece, ensures the convenience of welding and the repeatability of welds. Device is equipped with a special base that enables transport with a forklift. Thanks to this, we have obtained high mobility of the machine, which is extremely important in production halls. An additional advantage is the control system based on an inverter, which guarantees the reliability of the device.

Advantages:

- smooth speed control and selection of the direction of rotation
- adjustment of the disc in the range of 0-90°
- position setting with spring handle
- emergency stop - safety button on the control pendant

- current load of the built-in ground connection over a 60% cycle 200A.

## Technical details

|                   |                           |
|-------------------|---------------------------|
| Load capacity     | 150kg                     |
| Plate diameter    | 400mm                     |
| Rotation speed    | 0.12-1.2 / 0.5-5 obr/min  |
| Manual table tilt | 90°                       |
| Input             | ~1× 230V ± 10% 50 / 60 Hz |
| Weight            | 80kg                      |