



Product variants

Index	Price
FERROS 3D mobile lift welding table 2000 x 1000 (electrohydraulic version) SP28C-20-10-PE	€10,790.48 / pc Net price
FERROS 3D mobile lift welding table 2400 x 1200 (electrohydraulic version) SP28C-24-12-PE	€13,806.35 / pc Net price

Product description

USE THE SPACE FOR MORE EFFECTIVE WORK OFFERED BY FERROS TABLES!

- **EN-GJL-300 CAST IRON**
The casting of the top is made of EN-GJL-300 high strength cast iron characterized by high wear resistance.
- **25mm TABLE TOP**
The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.
- **MILLIMETRIC SCALE**
The applied millimeter scale facilitates precise assembly of the element to be processed.
- **D28 SYSTEM**
Drilled and chamfered holes 28mm.



The use of SPARTUS® mobile lift welding tables brings many benefits that translate into more effective and comfortable work.



facilitate element assembly.

- **MOBILITY**

High loads and tough working conditions on shop floors require the application of appropriate equipment. **The lift system uses wheels, including two with a braking system**, supporting safe and trouble-free movement of the welding table.

- **SAFETY**

The mobile lift is equipped with two protections:

- **maintenance interlocking system**



- **HEIGHT PRECISE ADJUSTMENT**

Setting the table top at the right customised height enhances the level of comfort during the performance of lengthy tasks, which has a significant impact on the work efficiency and welding quality. The working height of the lift (without the table top) is adjustable in the range from **530mm to 1000mm**.



- **LIFT CAPACITY**

Lifting system with a **high capacity of maximum 2200kg** (without the table top) allows you to load the unit with large-size elements and apply accessories to

- **limit switch** - crushing protection



The **SPARTUS® mobile lift welding tables** is a modern and convenient solution for professionals who value solid solutions that facilitate the work of welders.

Technical details

Size of the work surface	2000 x 1000 x 200mm
Made	casted
Material	EN-GJL-300 cast iron acc. to EN 1561
Table top thickness	25mm
Table horizontal precision	0.1/1000mm
Table vertical precision	0.1/200mm
Standard	D28 (drilled and milled holes 28mm diameter)
Supporting structure	Table lift
Nominal capacity (table top + details)	2200 kg
Carrying capacity with tabletop	1480 kg
Total table height	730 - 1200mm
Lifting	electro-hydraulic

Lifting speed	30mm/s
Lowering speed	40mm/s
Maximum number of lifting cycles	10/h
Table top weight	720kg
Jack weight	450kg
Input	~3× 400V ± 10% 50 / 60 Hz
