

product code: SP28W-20-10-PE



## Product variants

Index	Price
<b>HERMES 3D mobile lift welding table 2000 x 1000 (electrohydraulic version)</b> SP28W-20-10-PE	<b>€11,012.70 / pc</b> Net price
<b>HERMES 3D mobile lift welding table 2400 x 1200 (electrohydraulic version)</b> SP28W-24-12-PE	<b>€14,123.81 / pc</b> Net price

## Product description

### RELY ON COMFORT DURING WELDING, BY USING THE HERMES TABLES!

- **S355J2+N STEEL**  
Welding table top is made of S355J2+N steel grade, which is characterized by high strength and resistance to impact and deformation, and also provides protection against corrosion and weld spatter.
- **25mm TABLE TOP**  
The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.
- **MILLIMETRIC SCALE**  
The applied millimeter scale facilitates precise assembly of the element to be processed.
- **D28 SYSTEM**  
Drilled and chamfered holes 28mm.



The use of SPARTUS® mobile lift welding tables brings many benefits that translate into more effective and comfortable work.



facilitate element assembly.

- **MOBILITY**

High loads and tough working conditions on shop floors require the application of appropriate equipment. **The lift system uses wheels, including two with a braking system**, supporting safe and trouble-free movement of the welding table.

- **SAFETY**

The mobile lift is equipped with two protections:

- **maintenance interlocking system**



- **HEIGHT PRECISE ADJUSTMENT**

Setting the table top at the right customised height enhances the level of comfort during the performance of lengthy tasks, which has a significant impact on the work efficiency and welding quality. The working height of the lift (without the table top) is adjustable in the range from **530mm to 1000mm**.



- **LIFT CAPACITY**

Lifting system with a **high capacity of maximum 2200kg** (without the table top) allows you to load the unit with large-size elements and apply accessories to

- **limit switch** - crushing protection



The **SPARTUS® mobile lift welding tables** is a modern and convenient solution for professionals who value solid solutions that facilitate the work of welders.

## Technical details

Size of the work surface	<b>2000 x 1000 x 200mm</b>
Made	<b>welded</b>
Material	<b>S355J2+N steel acc. to EN 10025-2</b>
Table top thickness	<b>25mm</b>
Table horizontal precision	<b>0.1/1000mm</b>
Table vertical precision	<b>0.1/200mm</b>
Standard	<b>D28 (drilled and milled holes 28mm diameter)</b>
Supporting structure	<b>Table lift</b>
Nominal capacity (table top + details)	<b>2200 kg</b>
Carrying capacity with tabletop	<b>1480 kg</b>
Total table height	<b>730 - 1200mm</b>
Lifting	<b>electro-hydraulic</b>

---

<b>Lifting speed</b>	<b>30mm/s</b>
<b>Lowering speed</b>	<b>40mm/s</b>
<b>Maximum number of lifting cycles</b>	<b>10/h</b>
<b>Table top weight</b>	<b>720kg</b>
<b>Jack weight</b>	<b>450kg</b>
<b>Input</b>	<b>~3× 400V ± 10% 50 / 60 Hz</b>

---