Product details: ProMIG 535DP configurator





product code: B2B-BAZA-KPL-PROMIG535DP

The Pro machine configurator allows you to create a custom package.

BASE contains: ProMIG 535DP source; separated wire feeder 4R; cooler and driving set

In the other dictionaries, you can configure the remaining equipment options.

Product variants

Index

ProMIG 535DP configurator B2B-BAZA-KPL-PROMIG535DP

Product description

SYNERGIC MIG WITH DUAL PULSE

SPARTUS[®] **ProMIG 535 DP** is high-end, modern inverter welding machine constructed on the basis of advanced PWM technology and professional IGBT transistors. It enables MIG / TIG DC and MMA welding with a current up to 500A. It is powered from three phase 400V source power. The device offers a wide range of possibilities for the above-mentioned methods of joining metals.

MIG welding

ProMIG 535 DP is equipped with a synergistic system for MIG / MAG welding with the possibility of selecting the following programs: for mill steel, stainless steel, aluminum welding and braze welding. It is possible to manually correct the parameters. In addition, the device has a number of functionalities supporting the welding process in the MIG method:

- 1P (Pulse) MIG/MAG welding with pulsation, which significantly facilitates obtaining a spray arc,
- 2P (Dual Pulse) MIG/MAG welding with dual pulse, in TIG quality,
- JOB mode save and call 10 different job records,
- 2T/4T / s4T / SPOT Trigger Control,
- Burn Back,
- Slow Feed,
- Pre Gas and Post Gas.

Separate high-class four-roller feeder ensures stable wire feeding. An additional advantage is also the possibility of welding with the Spool Gun.

TIG welding

Thanks to the solutions used, the ProMIG 535 DP also enables advanced welding with the TIG Lift method.

ProMIG 535 DP has functions supporting the welding process in TIG method:

- 2T/4T Trigger Control,
- Down Slope.

MMA welding

The process of joining metals in this method is additionally supported by functions such as:

- Arc Force

- Hot Start.

Modern design, LCD function panel and the possibility of wireless control in combination with high-class components makes the SPARTUS[®] ProMIG 535 DP stand out on the market. The professional device of the **SPARTUS[®] Pro** line is perfect suited to the production sector and industry.

Technical details

Input	~3× 400V ± 10% 50 / 60 Hz
MIG welding current	10-500A
MIG duty cycle	60%
Wire feeder	separated, 4 - roll gear
Wire feeding speed	1.5 - 24 m/min
Welding wire spool	≤ 15kg / Ø200/300mm
Wire diameter	0.8 / 1.0 / 1.2 / 1.6mm
Synergy	yes
2T/4T Control	yes
s4T control	yes
SPOT welding	yes
	DUAL PULSE, Burn Back, Pre-gas, Post-gas, synergistic program, manual
Additional MIG functions	adjustment of parameters, inductance control, spool gun, Slow Feed, gas
	test, wire test
Water cooler	yes
Water cooler Tank capacity	yes 5l
Tank capacity	51
Tank capacity TIG Lift	51 yes
Tank capacity TIG Lift TIG welding current	51 yes 10 - 500A
Tank capacity TIG Lift TIG welding current Down slope	51 yes 10 - 500A 0 - 10s
Tank capacity TIG Lift TIG welding current Down slope MMA welding current	5i yes 10 - 500A 0 - 10s 10 - 500A
Tank capacity TIG Lift TIG welding current Down slope MMA welding current Arc Force	5 yes 10 - 500A 0 - 10s 10 - 500A yes
Tank capacity TIG Lift TIG welding current Down slope MMA welding current Arc Force Hot Start	5 yes 10 - 500A 0 - 10s 10 - 500A yes yes
Tank capacity TIG Lift TIG welding current Down slope MMA welding current Arc Force Hot Start Current consumpiton	5 5 9 9 9 10 - 500A 0 - 10s 10 - 500A 10 - 500A 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
Tank capacityTIG LiftTIG welding currentDown slopeMMA welding currentArc ForceHot StartCurrent consumpitonPower factor (cosφ)	5 5 yes 10 - 500A 0 - 10s 10 - 500A yes yes MIG 41.4A / TIG DC 34.4 / MMA 41.8A 0.75
Tank capacityTIG LiftTIG welding currentDown slopeMMA welding currentArc ForceHot StartCurrent consumpitonPower factor (cosφ)Insulation class	5 5 yes 10 - 500A 0 - 10s 10 - 500A yes yes MIG 41.4A / TIG DC 34.4 / MMA 41.8A 0.75 H