



product code: **B2B-BAZA-KPL-PROTIG321PDC**

The Pro machine configurator allows you to create a custom package.

BASE contains: ProTIG 321P DC source

In the other dictionaries, you can configure the remaining equipment options.

Product variants

Index	Price
ProTIG 321P DC configurator B2B-BAZA-KPL-PROTIG321PDC	€788.31 / pc Net price
ProTIG 2000 AC/DC configurator B2B-BAZA-KPL-PROTIG2000ACDC	€862.71 / pc Net price
ProTIG 2000W AC/DC configurator B2B-BAZA-KPL-PROTIG2000WACDC	€1,606.67 / pc Net price
ProTIG 220P AC/DC configurator B2B-BAZA-KPL-PROTIG220PACDC	€794.25 / pc Net price
ProTIG 225P AC/DC configurator B2B-BAZA-KPL-PROTIG225PACDC	€1,011.49 / pc Net price
ProTIG 3000 DC configurator B2B-BAZA-KPL-PROTIG3000DC	€743.67 / pc Net price
ProTIG 3000W DC configurator B2B-BAZA-KPL-PROTIG3000WDC	€1,487.63 / pc Net price
ProTIG 321PW DC configurator B2B-BAZA-KPL-PROTIG321PWDC	€1,678.71 / pc Net price
ProTIG 325P AC/DC configurator B2B-BAZA-KPL-PROTIG325PACDC	€1,443.00 / pc Net price
ProTIG 325PW AC/DC configurator B2B-BAZA-KPL-PROTIG325PWACDC	€2,333.40 / pc Net price
ProTIG 401P AC/DC configurator B2B-BAZA-KPL-PROTIG401PACDC	€2,067.92 / pc Net price
ProTIG 401PW AC/DC configurator B2B-BAZA-KPL-PROTIG401PWACDC	€2,958.33 / pc Net price
ProTIG 220P AC/DC configurator B2B-BAZA-PROTIG220PACDC	€794.25 / pc Net price

Index	Price
ProTIG 225P AC/DC configurator B2B-BAZA-PROTIG225PACDC	€1,011.49 / pc Net price
ProTIG 321P DC configurator B2B-BAZA-PROTIG321PDC	€788.31 / pc Net price
ProTIG 321PW DC configurator B2B-BAZA-PROTIG321PWDC	€1,678.71 / pc Net price
ProTIG 401P AC/DC configurator B2B-BAZA-PROTIG401PACDC	€2,067.92 / pc Net price
ProTIG 401PW AC/DC configurator B2B-BAZA-PROTIG401PWACDC	€2,958.33 / pc Net price

Product description

INDUSTRIAL TIG PULS

SPARTUS® ProTIG 321P DC it is a modern inverter welder adopts the latest pulse width modulation PWM technology and transistor IGBT power module.

It allows TIG DC and MMA DC welding with current up to 320A. It is powered from a 400V three-phase network.

The high-class source allows you to set the following parameters in the TIG method:

- Up Slope / Down Slope time,
- for TIG Puls: Puls Current, Base Current, Pulse Frequency, Pulse Width,
- mode selection 2T/4T / SPOT,
- Pre Gas, Post Gas,

in the MMA method:

- welding current,
- Arc Force,
- Hot Start.

All settings SPARTUS® ProTIG 321P DC are regulated by a modern LCD display. This not only facilitates control, but also allows for the precise setting and control of advanced functions due to the fact that the parameters can be continuously and steplessly adjusted.

Thanks to the TIG Puls function, the device is perfect for welding very thin sheets. ProTIG 321P DC has 10 memory channels. The user can easily save and recall the most used settings.

Modern design, LCD function panel and the possibility of wireless control in combination with high-class components makes the ProTIG 321P DC stand out on the market.

The professional device of the SPARTUS® Pro line is perfect suited to the production sector and industry.

Technical details

Input	~3× 400V ± 10% 50 / 60 Hz
TIG welding current	10 - 320A
TIG duty cycle	60%
Gas pre flow	0.1 - 2s
Gas post flow	0 - 10s
Up slope	0 - 10s
Down slope	0 - 10s
TIG Pulse	yes
Pulse Amps	10 - 320A
Pulse Width	5 - 95%
Pulse frequency	0,5 - 999Hz
2T/4T Control	yes
Arc ignition	HF
Control options	control in torch UP&DOWN, wired foot control, control in the handle potentiometer
MMA welding current	10 - 320A
Arc Force	yes
Hot Start	yes
No-load voltage	72.6V
Current consumpition	DC: TIG 18A / MMA 23.8A
Power factor (cosφ)	0.7
Efficiency η	85%
Insulation class	H
Protection class	IP21S
Weight	27.5kg
Dimensions	690 × 260 × 490mm
Control plug	9SPA - SPARTUS®