



product code: **B2B-BAZA-KPL-PROTIG321PWDC**

The Pro machine configurator allows you to create a custom package.

**BASE contains: ProTIG 321P DC source: coller and driving set**

In the other dictionaries, you can configure the remaining equipment options.

## Product variants

Index	Price
<b>ProTIG 321PW DC configurator</b> B2B-BAZA-KPL-PROTIG321PWDC	<b>€1,678.71</b> / pc Net price
<b>ProTIG 2000 AC/DC configurator</b> B2B-BAZA-KPL-PROTIG2000ACDC	<b>€862.71</b> / pc Net price
<b>ProTIG 2000W AC/DC configurator</b> B2B-BAZA-KPL-PROTIG2000WACDC	<b>€1,606.67</b> / pc Net price
<b>ProTIG 220P AC/DC configurator</b> B2B-BAZA-KPL-PROTIG220PACDC	<b>€794.25</b> / pc Net price
<b>ProTIG 225P AC/DC configurator</b> B2B-BAZA-KPL-PROTIG225PACDC	<b>€1,011.49</b> / pc Net price
<b>ProTIG 3000 DC configurator</b> B2B-BAZA-KPL-PROTIG3000DC	<b>€743.67</b> / pc Net price
<b>ProTIG 3000W DC configurator</b> B2B-BAZA-KPL-PROTIG3000WDC	<b>€1,487.63</b> / pc Net price
<b>ProTIG 321P DC configurator</b> B2B-BAZA-KPL-PROTIG321PDC	<b>€788.31</b> / pc Net price
<b>ProTIG 325P AC/DC configurator</b> B2B-BAZA-KPL-PROTIG325PACDC	<b>€1,443.00</b> / pc Net price
<b>ProTIG 325PW AC/DC configurator</b> B2B-BAZA-KPL-PROTIG325PWACDC	<b>€2,333.40</b> / pc Net price
<b>ProTIG 401P AC/DC configurator</b> B2B-BAZA-KPL-PROTIG401PACDC	<b>€2,067.92</b> / pc Net price
<b>ProTIG 401PW AC/DC configurator</b> B2B-BAZA-KPL-PROTIG401PWACDC	<b>€2,958.33</b> / pc Net price
<b>ProTIG 220P AC/DC configurator</b> B2B-BAZA-PROTIG220PACDC	<b>€794.25</b> / pc Net price

Index	Price
<b>ProTIG 225P AC/DC configurator</b> B2B-BAZA-PROTIG225PACDC	<b>€1,011.49 / pc</b> Net price
<b>ProTIG 321P DC configurator</b> B2B-BAZA-PROTIG321PDC	<b>€788.31 / pc</b> Net price
<b>ProTIG 321PW DC configurator</b> B2B-BAZA-PROTIG321PWDC	<b>€1,678.71 / pc</b> Net price
<b>ProTIG 401P AC/DC configurator</b> B2B-BAZA-PROTIG401PACDC	<b>€2,067.92 / pc</b> Net price
<b>ProTIG 401PW AC/DC configurator</b> B2B-BAZA-PROTIG401PWACDC	<b>€2,958.33 / pc</b> Net price

## Product description

### INDUSTRIAL TIG PULS

**SPARTUS® ProTIG 321PW DC** it is a modern inverter welder adopts the latest pulse width modulation PWM technology and transistor IGBT power module.

It allows TIG DC and MMA DC welding with current up to 320A. It is powered from a 400V three-phase network.

The high-class source allows you to set the following parameters in the TIG method:

- Up Slope / Down Slope time,
- for TIG Puls: Puls Current, Base Current, Pulse Frequency, Pulse Width,
- mode selection 2T/4T / SPOT,
- Pre Gas, Post Gas,

in the MMA method:

- welding current,
- Arc Force,
- Hot Start.

All settings SPARTUS® ProTIG 321PW DC are regulated by a modern LCD display. This not only facilitates control, but also allows for the precise setting and control of advanced functions due to the fact that the parameters can be continuously and steplessly adjusted.

Thanks to the TIG Puls function, the device is perfect for welding very thin sheets. ProTIG 321PW DC has 10 memory channels. The user can easily save and recall the most used settings.

The ProTIG 321PW DC model is additionally equipped with an integrated liquid cooler, which ensures efficient cooling of the torch during welding with high currents. The whole is placed on a transport cart with space for a shielding gas cylinder.

Modern design, LCD function panel and the possibility of wireless control in combination with high-class components makes the ProTIG 321PW DC stand out on the market.

The professional device of the SPARTUS® Pro line is perfect suited to the production sector and industry.

## Technical details

## Technical details

Input	~3× 400V ± 10% 50 / 60 Hz
TIG welding current	10 - 320A
TIG duty cycle	60%
Gas pre flow	0.1 - 2s
Gas post flow	0 - 10s
Up slope	0 - 10s
Down slope	0 - 10s
TIG Pulse	yes
Pulse Amps	10 - 320A
Pulse Width	5 - 95%
2T/4T Control	yes
Arc ignition	HF
Control options	control in torch UP&DOWN, wired foot control, control in the handle potentiometer
Water cooler	yes
Tank capacity	5l
MMA welding current	10 - 320A
Arc Force	yes
Hot Start	yes
No-load voltage	72.6V
Current consumpition	DC: TIG 18A / MMA 23.8A
Power factor (cosφ)	0.7
Efficiency η	85%
Insulation class	H
Protection class	IP21S
Weight	74.5kg
Dimensions	1150 x 600 x 1200mm
Control plug	9SPA - SPARTUS®