



product code: **B2B-BAZA-KPL-PROTIG401PACDC**

The Pro machine configurator allows you to create a custom package.

BASE contains: **ProTIG 401P AC/DC source**

In the other dictionaries, you can configure the remaining equipment options.

Product variants

Index	Price
ProTIG 401P AC/DC configurator B2B-BAZA-KPL-PROTIG401PACDC	€2,067.92 / pc Net price
ProTIG 2000 AC/DC configurator B2B-BAZA-KPL-PROTIG2000ACDC	€862.71 / pc Net price
ProTIG 2000W AC/DC configurator B2B-BAZA-KPL-PROTIG2000WACDC	€1,606.67 / pc Net price
ProTIG 220P AC/DC configurator B2B-BAZA-KPL-PROTIG220PACDC	€794.25 / pc Net price
ProTIG 225P AC/DC configurator B2B-BAZA-KPL-PROTIG225PACDC	€1,011.49 / pc Net price
ProTIG 3000 DC configurator B2B-BAZA-KPL-PROTIG3000DC	€743.67 / pc Net price
ProTIG 3000W DC configurator B2B-BAZA-KPL-PROTIG3000WDC	€1,487.63 / pc Net price
ProTIG 321P DC configurator B2B-BAZA-KPL-PROTIG321PDC	€788.31 / pc Net price
ProTIG 321PW DC configurator B2B-BAZA-KPL-PROTIG321PWDC	€1,678.71 / pc Net price
ProTIG 325P AC/DC configurator B2B-BAZA-KPL-PROTIG325PACDC	€1,443.00 / pc Net price
ProTIG 325PW AC/DC configurator B2B-BAZA-KPL-PROTIG325PWACDC	€2,333.40 / pc Net price
ProTIG 401PW AC/DC configurator B2B-BAZA-KPL-PROTIG401PWACDC	€2,958.33 / pc Net price
ProTIG 220P AC/DC configurator B2B-BAZA-PROTIG220PACDC	€794.25 / pc Net price

Index	Price
ProTIG 225P AC/DC configurator B2B-BAZA-PROTIG225PACDC	€1,011.49 / pc Net price
ProTIG 321P DC configurator B2B-BAZA-PROTIG321PDC	€788.31 / pc Net price
ProTIG 321PW DC configurator B2B-BAZA-PROTIG321PWDC	€1,678.71 / pc Net price
ProTIG 401P AC/DC configurator B2B-BAZA-PROTIG401PACDC	€2,067.92 / pc Net price
ProTIG 401PW AC/DC configurator B2B-BAZA-PROTIG401PWACDC	€2,958.33 / pc Net price

Product description

STRONG AND FOOLPROOF TIG AC/DC WITH PULSE

SPARTUS® ProTIG 401P AC/DC is a inverter welder in a modern edition. It allows TIG AC/DC and MMA AC/DC welding with current up to 400A. The device is powered from a 400V three-phase network.

Thanks to the solutions used, the ProTIG 401P AC/DC also enables advanced TIG AC and TIG DC welding with a choice of arc ignition HF or Lift method. The device is equipped with a pulse welding function, which makes the machine perfect for welding very thin sheets and aluminum.

ProTIG 401P AC/DC has functions supporting the welding process in TIG method:

- **output AC waveforms:** square, sinusoidal, triangular,
- **2T/4T** Trigger Control,
- **AC balance, AC frequency, pulse frequency, pulse** width and pulse amps adjustment,
- **up slope** and **down slope** adjustment,
- **SPOT** welding.

ProTIG 401P AC/DC enables MMA AC and MMA DC welding. The process of joining metals in this method is additionally supported by functions such as:

- **Arc Force**
- **Hot Start.**

Additionally the device has 10 memory channels. The user can easily save and recall the most used settings.

Modern design, LCD function panel and the possibility of wireless control in combination with high-class components makes the ProTIG 401P AC/DC stand out on the market.

The professional device of the SPARTUS® Pro line is perfect suited to the production sector and industry.

Technical details

Input	~3× 400V ± 10% 50 / 60 Hz
TIG welding current	10 - 400A
TIG duty cycle	60%
Gas pre flow	0.1 - 2s
Gas post flow	0 - 10s
Up slope	0 - 10s

Down slope	0 - 10s
TIG Pulse	yes
Pulse Amps	10 - 400A
Pulse Width	5 - 95%
Pulse frequency	0.5 - 999Hz
AC frequency	50 - 250Hz
AC wave forms	square, sinusoidal, triangular
AC balance	10 - 99%
2T/4T Control	yes
Arc ignition	HF, without HF
Control options	control in torch UP&DOWN, wired foot control, wireless remote control
MMA welding current	10 - 400
Arc Force	yes
Hot Start	yes
No-load voltage	74V
Current consumpition	AC: TIG 25.1 / MMA 19.4 DC: TIG 25.7 / MMA 32.7
Power factor (cosφ)	0.7
Efficiency η	85%
Insulation class	H
Protection class	IP21S
Weight	31kg
Dimensions	700 × 260 × 480mm
Control plug	9SPA - SPARTUS®