



TECHNICAL PARAMETERS

Input [V]	Welding current [A]	Duty cycle MIG [%]	Wire feeder	Welding wire spool [kg]/[mm]	Wire diameter [mm]	Weight [kg]	Dimensions [mm]
230	MIG 40 – 200 TIG 20 – 160 MMA 20 – 160	60	built-in 2 - roll gear	≤ 5 / Ø200	0.6 / 0.8 / 1.0	10	400 × 195 × 270

Additional features: 2T/4T, inductance, polarity change, BURN BACK, voltage compensation

DESCRIPTION

SPARTUS® EasyMIG 200 is a semi-automatic welding machine made in inverter technology. Allows welding in an inert and active gas shield (MIG/MAG), coated electrode (MMA) and TIG Lift with arc ignition.

Maximum welding current for MIG method is 200A, and for MMA and TIG Lift – 160A. The unit is powered from a single-phase network 230V.


The easy-to-use control panel allows for quick adjustment of welding parameters. EasyMIG 200 is characterized by a simple synergy in which only the wire diameter is determined for the selected gas. The device has functions supporting the welding process: 2T/4T, Burn Back, inductance adjustment, voltage compensation.

WIRE FEEDER

Light EasyMIG is equipped with a two-roll welding wire feeder, which ensures smooth and even feeding of the welding wire.



SPARTUS® EasyMIG 200



EASY

PACKAGE EQUIPMENT:

MIG gun SPARTUS® SPE 150 3m
electrode holder
work camp
gas hose
user's manual

