



spartus.info

ProVent M - mobile welding fume extractor

SP030-07-00M • Filtration surface area: 12 m² • Fan: 1.1 kW – 1 phase, 400 V

Mobile welding fume extractor designed for the extraction of dry dust.

Standard construction:

- 1.1 kW radial fan
- two-stage filtration
- main filter regeneration system with manual control
- · powder-coated, welded steel housing
- dust drawer
- 10 I compressed air tank
- rubber mat

Specifications:

Nominal air flow: 1000 m³/h
Filtration surface area: 12 m²
Weight: 110 kg
Power supply: 3 x 400V / 50Hz
Motor power: 1,1 kW

Rated current: 2,7 A

Accessories and options:


Vortex 160 extraction arm, 2 m reach, Ø315 mm nozzle inlet Vortex 160 extraction arm, 3 m reach, Ø315 mm nozzle inlet main filter regeneration system with timer control

Spare parts:

• main [patron] filter 6 m²

metal pre-filter

Packing method and carton dimensions:



A = 610 B = 1200 H = 1050 weight = 110 kg

All dimensions are given in mm

NOV-WELD Sp. z o.o. Miszewko, Słoneczna 9, 80-297 Banino Phone: +48 58 341 3417, Fax: +48 58 345 7946 Email: nowweld@nowweld.pl

All rights reserved. This document and the designs, technical data, and trademarks it contains are protected and remain the property of the manufacturer. The manufacturer reserves the right to introduce design changes without prior notice.

