



• spartus.info

Vortex 160 extraction arm, standing model

SP030-10-162P

- Diameter: 160 mm, reach: 2.0 m
- Suction nozzle inlet: 315 mm
- Standing model

Standard construction:


- Recommended airflow: $900 \div 1400 \text{ m}^3/\text{h}$
- External adjustment components
- Aluminum suction nozzle with inlet damper
- Handle surrounding the entire nozzle
- Aluminum suction joints
- Cast aluminum middle joints and base socket
- Aluminum-steel socket
- Rolled steel pipes
- Built-in aluminum damper in the duct
- Black flexible PVC hoses resistant to temperatures up to 80°C
- Standard powder-coated finish

Accessories and options:

- Mounting bracket
- Mounting bracket (longer version)
- Circular connection stub $\varnothing 160 \text{ mm}$, steel
- Set SP030-99-002 (photocell, suction head lighting, switch, 8 m cable)
- Set SP030-99-001 (suction head lighting, switch, 8 m cable)
- Grounding cable set with pipe and socket connection
- Enlarged nozzle, complete $\varnothing 160 \text{ mm} / 500 \text{ mm}$

Notes:

Packaging and box dimensions:



A = 360
B = 1470
H = 630
gross weight = 21 kg

All dimensions are given in **mm**

NOV-WELD Sp. z o.o.
Miszewko, Słoneczna 9, 80-297 Banino
phone: +48 58 341 3417, fax: +48 58 345 7946
email: noweld@noweld.pl



All rights reserved. This document and the data, technical drawings, and trademarks contained within are protected and remain the property of the manufacturer. The manufacturer reserves the right to introduce design changes without prior notice.

